

AGRICULTURAL IRRIGATION | *A Hunter Industries Company*
LOW PRESSURE - HIGH PERFORMANCE



- 01 **Abrasion Resistance**
- 02 **Polyester:** Reinforced Yarns
- 03 **Pressure range:** 0 to 100 psi
(0 to 6.89 bar)
- 04 **Lightweight:**
non-marking, flexible

REINFORCED PVC HOSE

3/4" PVC Flex Hose

Senninger uses proven technology to provide an extremely durable hose that is ideal for agricultural irrigation systems.



FEATURES, DATA AND COMPONENTS

FEATURES

- Temperature range: +25°F to +150°F (-4°C to +66°C)
- ISO 9001 manufacturing standards
- Two-year warranty



ADDITIONAL COMPONENTS



Model Number	ProductDescription
HSC40ET	hose clamp
FTA3F3B	hose barb fitting
FTA3M3B	hose barb fitting
HSCTOET497	crimping tool

Model Number	Inside Diameter	Outside Diameter	Working Pressure @ 68°F or 20°C	Weight per 100 ft. (30.48 m)	Standard Package
HS3RA	0.795 in. (20.19 mm)	0.975 in. (24.77 mm)	0-100 psi (0-6.89 bar)	16 lbs. (7.26 kg)	250 ft. coil (76.2 m coil)

Estimated burst pressure 300 psi (20.7 bar)

Website senninger.com | Customer Support 407-877-5655

Senninger's commitment to world-class products, local support and technical expertise ensure we provide the most efficient and reliable agricultural irrigation solutions available in the world today.

Steve Abernethy, President of Senninger Irrigation