











# MICRO-SPRINKLERS INSTALLATION OPTIONS

LOW PRESSURE	HIGH PRESSURE
MISIDA24NDVL* ASSEMBLY EXCLUDING APPLICATOR	MISIDA24NDVH* ASSEMBLY EXCLUDING APPLICATOR
MR250DB ¼" Double Barb Connector 	MR250DB ¼" Double Barb Connector 
TUV250* 2ft. (0.61 m) 0.25" Tubing (black) 	TUV250* 2ft. (0.61 m) 0.25" Tubing (black) 
MRWGT1OZ PE Slip-Over Weight (1 oz) 	MRWGT1OZ PE Slip-Over Weight (1 oz) 
FOG250NXB ¼" Nipple x ¼" Barb Connector 	FOG250NXB ¼" Nipple x ¼" Barb Connector 
MISINDVL Non-Drip Valve (low pressure) 0.25" F x M Press-Fit (opens at 14.5 psi (1 bar)) 	MISINDVH Non-Drip Valve (high pressure) 0.25" F x M Press-Fit (opens at 21.7 psi (1.5 bar)) 

RSST26	RSST14
Riser Stake 26" Connection for tubing or Riser Adapter 	Riser Stake 14" Connection for tubing or Riser Adapter 

Use with Inverted Micro-Sprinklers 3/8"  
BSW models #2, 3 or 4 nozzles (sold  
separately)  
\*24" length. (other lengths available).  
Contact customer service for part numbers  
and pricing.