

Mechanized Irrigation

LOW PRESSURE - HIGH PERFORMANCE™



AGRICULTURAL IRRIGATION | A Hunter Industries Company
Learn More. Visit senninger.com

Senninger®

Mechanized Irrigation



WOBLER®

i-Wob®2 (black)



Flow: 0,8 - 18,35 gpm (182 - 4168 L/hr)
Pressure: 6 - 15 psi (0,41 - 1,03 bar)
Droplet size: Medium

i-Wob®2 (grey)



Flow: 2,24 - 18,35 gpm (509 - 4168 L/hr)
Pressure: 6 - 15 psi (0,41 - 1,03 bar)
Droplet Size: Small

i-Wob®2 (blue)



Flow: 0,8 - 18,35 gpm (182 - 4168 L/hr)
Pressure: 6 - 15 psi (0,41 - 1,03 bar)
Droplet Size: Medium

i-Wob®2 (white)



Flow: 2,51 - 18,35 gpm (570 - 4168 L/hr)
Pressure: 6 - 15 psi (0,41 - 1,03 bar)
Droplet Size: Large

Xi-Wob™ (blue)



Flow: 1,09 - 15,78 gpm (248 - 3584 L/hr)
Pressure: 10 - 15 psi (0,69 - 1,03 bar)
Droplet Size: Medium

Xi-Wob™ (black)



Flow: 2,24 - 15,78 gpm (509 - 3584 L/hr)
Pressure: 10 - 15 psi (0,69 - 1,03 bar)
Droplet Size: Large

Xi-Wob™ (grey)



Flow: 2,24 - 15,78 gpm (509 - 3584 L/hr)
Pressure: 10 - 15 psi (0,69 - 1,03 bar)
Droplet Size: Small

Xcel-Wobler™ TOP



Flow: 0,8 - 14,98 gpm (182 - 3402 L/hr)
Pressure: 10 psi (0,69 bar)
Droplet Size: Large

LDN®

LDN®



Flow: 0,27 - 21,18 gpm (61 - 4815 L/hr)
Pressure: 6 - 20 psi (0,41 - 1,38 bar)
Several deflector pad options including part-circle

LDN® LEPA Bubbler



Flow: 0,27 - 18,35 gpm (61 - 4168 L/hr)
Pressure: 6 - 15 psi (0,41 - 1,03 bar)
Several deflector pad options

LDN® LEPA Shroud™



Flow: 0,27 - 18,35 gpm (61 - 4168 L/hr)
Pressure: 6 - 15 psi (0,41 - 1,03 bar)
Several deflector pad and insert options

LDN® LEPA Wide Spray Bubble



Flow: 0,35 - 5,08 gpm (79 - 1154 L/hr)
Pressure: 6 - 10 psi (0,41 - 0,69 bar)
Several deflector pad options

LDN® Dynamic Drive (top of pipe)



Flow: 0,8 - 33,49 gpm (182 - 7606 L/hr)
Pressure: 10 - 50 psi (0,69 - 3,45 bar)
Low and high pressure models

LDN® Dynamic Drive (hose drop)



Flow: 0,8 - 25,94 gpm (182 - 5892 L/hr)
Pressure: 10 - 30 psi (0,69 - 2,07 bar)
Low and high pressure models

LDN® Dynamic Drive (part-circle)



Flow: 1,43 - 8,79 gpm (325 - 1996 L/hr)
Pressure: 10 - 30 psi (0,69 - 2,07 bar)

IMPACT SPRINKLERS

Pivot Master®



Flow: 1,87 - 36,0 gpm (425 - 8177 L/hr)
Pressure: 30 - 60 psi (2,07 - 4,14 bar)

REGULATORS | SPRAYS | COMPONENTS

PRL



Flow: 0,5 - 8 gpm (114 - 1817 L/hr)
Pressure: 6 - 40 psi (0,41 - 2,76 bar)

PSR™2



Flow: 0,5 - 15 gpm (114 - 3407 L/hr)
Pressure: 6 - 50 psi (0,41 - 3,45 bar)

PMR-MF



Flow: 2 - 20 gpm (454 - 4542 L/hr)
Pressure: 6 - 60 psi (0,41 - 4,14 bar)

Filter Regulator



Flow: 0,7 - 4,66 (16 - 3811 L/hr)
Pressure: 6 - 20 psi (0,41 - 1,38 bar)

Super Spray®



Flow: 0,27 - 29,96 gpm (61 - 6805 L/hr)
Pressure: 6 - 40 psi (0,41 - 2,76 bar)
Several deflector pad options

End Spray



Flow: 8,1 - 48,9 gpm (1840 - 11106 L/hr)
Pressure: 10 - 25 psi (0,69 - 1,72 bar)

COMPONENTS

Universal Magnum Weight™



Fits all Senninger sprinklers used on hose drops

Goosenecks



Sgl max flow: 20 gpm (4542 L/hr)
Dbl max flow: 15 gpm (3406 L/hr) per side
Use Truss Rod Hose Slings with 125° degree models