

























PART NUMBERS FOR SENNINGER®

## Micro Drop Assemblies

MISIDA24NDVL	MISIDA24NDVH	FOGDA24375BSW4	FOGDA24375BSW	MISIDA24
<b>MAXSMJBBXB6</b> ¼" double barb connector 	<b>MAXSMJBBXB6</b> ¼" double barb connector 	<b>MAXSMJBBXB6</b> ¼" double barb connector 	<b>MAXSMJBBXB6</b> ¼" double barb connector 	<b>MAXSMJBBXB6</b> ¼" double barb connector 
<b>TUV250</b> 0.250" OD 24" length 	<b>TUV250</b> 0.250" OD 24" length 	<b>TUV250</b> 0.250" OD 24" length 	<b>TUV250</b> 0.250" OD 24" length 	<b>TUV250</b> 0.250" OD 24" length 
<b>MRWGT1OZ</b> PE slip-over weight (1 ounce) 	<b>MRWGT1OZ</b> PE slip-over weight (1 ounce) 	<b>MRWGT1OZ</b> PE slip-over weight (1 ounce) 	<b>MRWGT1OZ</b> PE slip-over weight (1 ounce) 	<b>MRWGT1OZ</b> PE slip-over weight (1 ounce) 
<b>FOG250NXB</b> ¼" nipple x ¼" barb connector 	<b>FOG250NXB</b> ¼" nipple x ¼" barb connector 	<b>FOG250NXB</b> ¼" nipple x ¼" barb connector 	<b>FOG250NXB</b> ¼" nipple x ¼" barb connector 	
<b>MISINDVL</b> non-drip valve 0.25" F x M press-fit (low pressure - opens at 14.5 psi or 1 bar) 	<b>MISINDVH</b> non-drip valve 0.25" F x M press-fit (high pressure - opens at 21.7 psi or 1.5 bar) 	<b>FOG4CROSS</b> 4-way cross adapter   <b>INCLUDES</b> 4 Foggers ⅜" BSW connection 	<b>INCLUDES</b> 1 Fogger ⅜" BSW connection 	
Above drop assembly excludes sprinkler	Above drop assembly excludes sprinkler			Above drop assembly excludes sprinkler