



- 01 **Reliable:** Wobbler® Technology in a top-of-pipe sprinkler
- 02 **Low Pressure:** 10 psi (0.69 bar)
- 03 **Convenient:** UP3® Nozzle
- 04 **Competitively Priced**

## XCEL-WOBBLER™ TOP FOR CENTER PIVOTS

*Reliable Wobbler® Technology provides outstanding uniformity over a large area which is ideal for high-profile crops*

Senninger expanded their patented Wobbler Technology for top-of-pipe with the Xcel-Wobbler employing their innovative UP3® nozzle. This sprinkler is designed for low pressure - 10 psi (0.69 bar) - to promote energy savings and a wind-resistant larger droplet size. The gentle rain-like application is suitable for all soils and various terrains.

# XCEL-WOBBLER™ TOP FEATURES & SPECIFICATIONS

## FEATURES:

- Outstanding uniformity using Wobbler® Technology
- Low pressure - 10 psi (0.69 bar) for energy savings
- UP3® easy change/clean nozzles in a full range of sizes for the entire length of the pivot (#6 to #26, including half sizes). Nozzles are warranted to maintain correct orifice size for five years.
- Two-year warranty on materials, workmanship and performance

## XCEL-WOBBLER TOP DESIGN CRITERIA


Nozzle Sizes	
Minimum	#6 3/32" (2.38 mm)
Maximum	#26 13/32" (10.32 mm)
Flows	
Minimum	0.80 gpm (182 L/hr)
Maximum	14.98 gpm (3402 L/hr)
Diameters	
Minimum at 12 ft ht (3.66 m)	43 ft (13.1 m)
Maximum at 12 ft ht (3.66 m)	51 ft (15.5 m)
Maximum Spacing at 12 ft ht (3.66 m) ground clearance	
	20 ft (6.1 m)
Pressure	
	10 psi (0.69 bar)



## INSTALLATION:

- The Xcel-Wobbler TOP requires a 10 psi (0.69 bar) pressure regulator. *Senninger PSR-2 is recommended.*
- Install with a 3/4" Galvanized, Stainless Steel or the Senninger impact modified thermoplastic nipple into the mainline (*maximum 2 ft length*).
- Designed specifically for upright installation on the top-of-pipe along a center pivot or other mechanical move system.
- The Xcel-Wobbler TOP is not recommended for a manifold installation of two or more units from a single outlet.

**NOTE: Any modifications or deletions regarding installation requirements will void product warranty.**



Website [senninger.com](http://senninger.com) | Customer Support +1 407-877-5655

The Senninger commitment to world-class products, local support and technical expertise ensure we provide the most efficient and reliable agricultural irrigation solutions available in the world today.

*Steve Abernethy*  
Steve Abernethy, President of Senninger Irrigation